

Our Patented DuraFlex[®] Locks & Keys

- ✓ Triangle quarter turn lock.
- ✓ Features a built in mechanical audible detent.
- ✓ A durable, non corrosive component.
- ✓ Can be fitted easily in seconds and will not drop out during use.
- ✓ Each lock is supplied with a vandal- & anti-theft proof nut.

50mm Locks



With 35mm hooked pawl
(HLLOCKS150)



With 35mm straight pawl
(HLLOCKS151)



With 45mm straight pawl
(HLLOCKS156)

60mm Locks



With 35mm hooked pawl
(HLLOCKS152)



With 35mm straight pawl
(HLLOCKS153)



With 55mm straight pawl
(HLLOCKS160)

Keys



Standard triangle key
(HLLOCKS154)

- Standard 8mm key insert
- length of shaft: 50mm
- Complies with EN840
- Supplied with out-of-service plug



Extended triangle key
(HLLOCKS157)

- Standard 8mm key insert
- length of shaft: 80mm

Accessories



Adaptor for Taylor lock hole
(HLLOCKS155)



Weather proof cap for all of our locks
(NL21)

FITTING INSTRUCTIONS:

Insert the lock through the lid lock hole. Initially, tighten the lock nut, then nip it with a spanner to ensure the auto-lock system is engaged. This will prevent the nut from working loose. Do not overtighten!